



TECHNICAL DATA				Pump type G25A.00			
Air supply pressure	0,2-0,7	MPa		Max. viscosity (neg. suc.)	3000	Cp	
Max. discharge volume/cycle	600	ml		Max. viscosity (flooded suction.)	8000	Cp	
Max. discharge volume	150	L/min		Max. air consumption	1400	NL/min	
Max. discharge pressure	0,7	MPa		Max. noise level	81	dB(a)	
Max. size of solids				Operating temp. ambient	0-70	°C	
Max. suction lift dry	PTFE fitted			Max operating temp. fluid			
Max. suction lift wet	PTFE fitted			Diaphragm compound	G25AN00	NBR	0-70 °C
Max. fluid inlet pressure	PTFE fitted		Mpa	Diaphragm compound	G25AH00	TPEE	0-80 °C
Max. suction lift dry	Rubber fitted	4,0	Mtr	Diaphragm compound	G25AS00	TPO	0-100 °C
Max. suction lift wet	Rubber fitted	5,5	Mtr				
Max. fluid inlet pressure	Rubber fitted	0,1	Mpa	Net Weight	Type A	ALU	9,2 Kg
Caution! Data based on water (1 Cp) under ambient temperature							
Wetted parts: Pump chambers + manifolds				ADC12 - Aluminum			
Motor				ADC12 - Aluminum			

